

[54] ACOUSTIC COORDINATE INPUT DEVICE
USING A ROUGHENED SURFACE TO
ATTENUATE THE SURFACE WAVE
COMPONENT

[75] Inventor: Shinnosuke Taniishi, Tokyo, Japan

[73] Assignee: Canon Kabushiki Kaisha, Tokyo,
Japan

[21] Appl. No.: 171,747

[22] Filed: Mar. 22, 1988

[30] Foreign Application Priority Data

Mar. 27, 1987 [JP] Japan 62-071400

Apr. 1, 1987 [JP] Japan 62-077547

[51] Int. Cl.⁴ G08C 21/00

[52] U.S. Cl. 178/18; 367/907;
340/706

[58] Field of Search 178/18, 19; 367/907,
367/117, 127; 340/706

[56] References Cited

U.S. PATENT DOCUMENTS

4,665,282 5/1987 Sato et al. 340/706 X

Primary Examiner—Stafford D. Schreyer

Attorney, Agent, or Firm—Fitzpatrick, Cella, Harper &
Scinto

[57] ABSTRACT

A coordinates input device comprises vibration means for generating vibration, a pin having an end to which the vibration generated by said vibration means is transmitted, and a vibration transmission plate having a roughened surface or resin coating on a pen abutment surface thereof, for transmitting the vibration.

8 Claims, 9 Drawing Sheets

